# **Cable Drum Stands**

High Quality Cable Drum Stands 500kg – 100 Tonne

**BUILT TOUGH, DESIGNED TO LAST!** 



Our expert sales and customer Service team can advise you on the Best product to suit your needs.

**Contact Neumann Equipment today.** 



(07) 5589 9746

### **Cable Drum Stands**

Neumann Equipment manufactures a range of standard cable drum stand units designed to hold electrical cable reels. A bolt together style for 0.5 to 5 tonne spindle capacity, and a fabricated style for all cable drum stands for drum weights of over 6 tonnes.

The bolt together style units have the advantage of being dis-assembled to save on transport and storage.

Cable drum stands, capable of handling drums up to 100 Tonnes, can also be custom-made to suit your requirements.

All of our cable drum stands designs are verified using Finite Element Analysis (FEA). They are Built Tough and Designed to Last!

### 1 to 100 Tonne Cable Drum Stands include:

- Shaft support bearings,
- Fabricated from grade 250 carbon steel,
- Rated lifting lugs on the spindle to facilitated drum replacement
- Rated lifting points on the frame to allow the drum stand to be positioned on site (Unloaded)
- Tapered spindle cones to allow various drum core diameters.
- Spindle clamps to lock various size drum widths in place.
- Mounting holes are incorporated in the base to allow the frame to fastened to a structure.
- Heavy duty industrial two-pack epoxy protective coating.

## **Standard Range of Cable Drum Stands in stock:**

| Model Number  | CDST500   | CDST1000  | CDST5000    | CDST12000     |
|---|-----------|-----------|-------------|---------------|
| Type (Bolted or Fabricated)                             | Bolted    | Bolted    | Bolted      | Fabricated    |
| Maximum Spindle Capacity                                | 500kg     | 1,000kg   | 5,000kg     | 12000kg       |
| Suit Drum Widths  | 350-800mm | 600-900mm | 900-1,250mm | 1,500-1,690mm |
| Maximum Drum Diameter                                   | 850mm     | 1,300mm   | 2,050mm     | 2,350mm       |
| Shaft Diameter  | 34mm      | 45mm      | 80mm        | 120mm         |
| Suit Drum Core  | 35mm+     | 46-120mm  | 81-120mm    | 121-250mm     |
| Frame Width   | 350-800m  | 1,066mm   | 1,550mm     | 2,350mm       |
| Frame Length  | 500mm     | 1,066mm   | 1,550mm     | 2,400mm       |
| Height to Centre Line of Shaft                          | 450mm     | 744mm     | 1,168mm     | 1,878mm       |
| Weight  | 24kg      | 78kg*     | 281kg*      | 892kg*        |
| * Weight does not include entional forked base or brake |           |           |             |               |

<sup>\*</sup> Weight does not include optional forked base or brake.

### **Available Options:**

- Forklift compatible base option for the 1 and 5 tonne models (bolt-on),
- Fork tyne slots are standard on all Cable Drum Stands for drum weights of over 6 tonnes.
- Optional manually adjusted friction brake for all models, except 500kg model.

Please contact us by phone or email to discuss your cable drum stand requirements

### Standard Cable Drum Stands



12 Tonne Cable Drum Stand Fully Fabricated and Welded



5 Tonne Cable Drum Stand
Bolt Together Style



1 Tonne Cable Drum Stand Bolt Together Style



500kg Cable Drum Stand
Bolt Together Style

#### **NEUMANN** EQUIPMENT

neuamannequipment.com.au

13 Nuban Street, Currumbin, Queensland 4223 Australia PO Box 8, Currumbin, Queensland 4223 Australia +61 7 5589 9746 equipment@neumann.com.au

